

EMBLEM Solvent Wall Decoration 170 Adhesive

EMBLEM Solvent Wall Decoration 170 Adhesive is a wallpaper based on non-woven paper for individual interior design. The matt, white surface of the wallpaper can be printed with standard eco solvent, solvent, latex and UV inks and is characterized by a soft feel. The back of the product is self-adhesive.

| | |
|--------------------------|---|
| Matchcode: | SOWADE170ADH |
| Material: | coated, non-woven paper, free of glass fibre |
| Finish: | matt |
| Color: | white |
| Weight: | 172 g/m ² ± 6 g/m ² - ISO 536 |
| Thickness: | 271 µm ± 8 µm - ISO 534 |
| Opacity: | > 90 % - ISO 2469 |
| CIE whiteness: | > 97 %, D65/10° - ISO 2469 |
| Adhesive: | water-based acrylic adhesive, permanent |
| Liner: | glassine liner, 65 g/m ² |
| Adhesion power: | N/A, final adhesion is achieved after 16-24 hours |
| Adhesion weight: | 40 g/m ² |
| Application temperature: | +20 °C - +25 °C |
| Flame retardant: | N/A |
| Standard roll width: | 152 cm |
| Standard roll length: | 30 m |
| Storage: | cool and dry at 15-25 °C, 50 % rel. humidity |
| Shelf life: | 12 months in original packing |

COMPATIBLE INKS:

| | | | | | |
|--------------|-----|--------|-----|------------|-----|
| Eco solvent: | yes | UVC: | yes | | |
| Solvent: | yes | Latex: | yes | Dry toner: | yes |

Different printers, inks, resolutions and printing qualities result into numerous different printing parameters. In addition, there are numerous factors influencing processing and the application of our materials. For this reason, we cannot make specific statements as to drying times and maximum ink absorption. For this reason, we recommend you to perform own tests in order to verify the desired results. Our product specifications are not to be understood as legally binding guarantees assuring specific characteristics. Any liabilities and guarantees, as well as claims for compensation beyond the value of the product itself are excluded.

EMBLEM Solvent Wall Decoration 170 Adhesive

Description:

EMBLEM Solvent Wall Decoration 170 Adhesive is a wallpaper based on non-woven paper for individual interior design. The matt, white surface of the wallpaper can be printed with standard eco solvent, solvent, latex and UV inks and is characterized by a soft feel. The back of the product is self-adhesive.

Due to the special surface you can achieve brilliant photorealistic prints with a high ink coverage. This product is free of PVC, plasticizers and solvents. Without the addition of heavy metal compounds and formaldehyde.

EMBLEM SOWADE170ADH is stable in dimension, crack-bridging and easy to apply. The wallpaper adheres to smooth wall surfaces or plasters painted with dispersion paint or primer.

Processing:

The prints are suitable for indoor decoration without lamination.

The wallpaper should acclimatize sufficiently (up to 48 hours) before it is glued. The substrate should be as well prepared as for wallpapering with paste and should correspond to quality level 3. This means that the substrate must be dry, clean, firm, absorbent and smooth. If necessary, the substrate should be primed. Existing paints, plasters or fillers must be thoroughly dried. Please refer to the manufacturer's instructions for guidance.

Multiple panels are hung edge-to-edge. The wallpaper can still be repositioned within the first 10 minutes. Press on the strips with sponge rubber roller or wallpapering brush without bubbles.

Application:

Typical applications for EMBLEM SOWADE170ADH are individual decoration for living spaces, children's rooms, shopping malls, museums, booth constructions, commercial buildings, hotels and restaurants, wall tattoos.