

EMBLEM Latex-UV Wall Decoration 150 Neo

EMBLEM Latex-UV Wall Decoration 150 Neo is a paper-based non-woven wallpaper for customised interior design. You can print on the soft, matt, neutral white surface of the non-woven wallpaper with commercially available latex and UVC inks. The EMBLEM LUVWADE150N is applied in the same way as standard non-woven wallpapers.

| | |
|-------------------------|---|
| Matchcode: | LUVWADE150N |
| Material: | coated paper fleece, free from glass fibres |
| Surface: | matt |
| Colour: | white |
| Weight: | 150 g/m ² |
| Thickness: | 190 µm |
| Processing temperature: | from 15 °C |
| Standard roll width: | 1370 mm |
| Standard roll length: | 50 m |
| Storage: | cool and dry environment, at 15-25 °C, 50 % rel. humidity |
| Shelf life: | 12 months in original packing |

COMPATIBLE INKS:

| | | | |
|--------------|----|--------|-----|
| Eco solvent: | no | UVC: | yes |
| Solvent: | no | Latex: | yes |

Different printers, inks, resolutions and printing qualities result into numerous different printing parameters. In addition, there are numerous factors influencing processing and the application of our materials. For this reason, we cannot make specific statements as to drying times and maximum ink absorption. For this reason, we recommend you to perform own tests in order to verify the desired results. Our product specifications are not to be understood as legally binding guarantees assuring specific characteristics. Any liabilities and guarantees, as well as claims for compensation beyond the value of the product itself are excluded.

EMBLEM Latex-UV Wall Decoration 150 Neo

Description:

EMBLEM Latex-UV Wall Decoration 150 Neo is a paper-based non-woven wallpaper for customised interior design. You can print on the soft, matt, neutral white surface of the non-woven wallpaper with commercially available latex and UVC inks. The wallpaper has a pleasantly soft feel and a noticeable non-woven texture that conveys a high level of quality.

On the LUVWADE150N you can create prints in photorealistic quality. It is free from PVC, plasticisers and solvents, without the addition of heavy metal compounds and formaldehyde.

EMBLEM LUVWADE150N has a high opacity and is crack-bridging. It is easy to apply. The wallpaper adheres to smooth, slightly rough wall surfaces painted with binder paint or plaster. It is also easy to remove when dry.

From an ecological point of view, LUVWADE150N is very environmentally friendly, PVC-free and made from renewable raw materials.

Processing:

The un laminated prints can be used indoors as decoration. For further processing as decorative wallpaper, the usual procedures for wallpapering apply. The substrate must be dry, clean, firm, absorbent and smooth. Usually you apply the wallpaper using the paste the wall technique. If there are several strips, they are glued together. If necessary, a double seam cut can be made when dry. Press down the strips with a foam rubber roller or wallpapering brush until bubble-free. Remove any excess adhesive immediately with a damp cloth or sponge.

To apply the wallpaper, we recommend using commercially available paste for non-woven wallpaper, such as Metylan Direct for non-woven wallpaper.

Application:

Typical applications for EMBLEM LUVWADE150N are individual room designs for living spaces, children's rooms, shopping centers, museums, exhibition stands, commercial spaces, hotels and restaurants.