

EMBLEM Solvent RollUp Film Silverback II

EMBLEM Solvent RollUp Film Silverback 2 is a special coated PET compound with a good flatness. The high opacity comes from the silver, metallic colored back side. The coating is featured by minor reflections, brilliant colors and a good scratch resistance. It can be printed on with usual eco solvent, solvent, latex and UVC inks.

Matchcode:	SORFSB2
Material:	PET compound with silver, metallic colored back side
Finish:	semimatt, slightly structured
Color:	white
Thickness:	200 μ m
Visual density:	2,7
Lamination:	cold, warm
Fire behaviour:	N/A
Standard roll width:	914 / 1067 / 1270 mm
Standard roll length:	30 m
Storage:	cool and dry at 15-25 °C, 50 % rel. humidity
Shelf life:	18 months in original packing

COMPATIBLE INKS:

Eco solvent:	yes	UVC:	yes
Solvent:	yes	Latex:	yes

Different printers, inks, resolutions and printing qualities result into numerous different printing parameters. In addition, there are numerous factors influencing processing and the application of our materials. For this reason, we cannot make specific statements as to drying times and maximum ink absorption. For this reason, we recommend you to perform own tests in order to verify the desired results. Our product specifications are not to be understood as legally binding guarantees assuring specific characteristics. Any liabilities and guarantees, as well as claims for compensation beyond the value of the product itself are excluded.

EMBLEM Solvent RollUp Film Silverback II

Description:

EMBLEM Solvent RollUp Film Silverback 2 is a special coated PET compound with a good flatness. The high opacity comes from the silver, metallic colored back side. The coating is featured by minor reflections, brilliant colors and a good scratch resistance. It can be printed on with usual eco solvent, solvent, latex and UVC inks. Because of the good flatness EMBLEM SORFSB2 has no side curl (tubing). Therefore it is the ideal solution for rollup systems.

Processing:

Before further processing the VOC's of solvent, eco-solvent and latex inks must be dried completely. The drying time depends on the amount of ink used. Solvent residue caused by insufficient drying time can lead to blocking if stored in rolled-up form. We advise to unroll the printed strip and spread it out as soon as possible until final drying or use the EMBLEM Easy Dryer for the drying process.

When the surface is subject to humidity, abrasion, sweat or other mechanical influences for a long time it must be protected with self-adhesive laminating films or appropriate liquid lamination products. During lamination such residues can impact the quality of the finished product (flatness, shrinkage behaviour, anchorage, adhesion power, etc) negatively.

Before printing check the correct drying temperature by carrying out a trial print. Drying temperatures which are too high can lead to a deformation of the film.

To avoid fingerprints the use of cotton gloves is advised.

Application:

Typical applications for SORFSB2 are rollup systems, L-displays, displays, POS, posters, signs, exhibition panels.