

EMBLEM Solvent Banner Heavy Block Out 780 FR

EMBLEM SOBBO780FR is a premium PVC banner based on a grey polyester fabric. This grey fabric guarantees high opacity and prevents even bright light from shining through. SOBBO780FR corresponds to fire protection classification B1. So it can be used in interiors.

| | |
|-------------------------|---|
| Matchcode: | SOBBO780FR |
| Material: | PVC cast banner based on grey fabric |
| Finish: | semimatt |
| Color: | white |
| Weight: | 780 g/m ² |
| Tensile strength: | 2900 / 2500 N/5 cm acc. DIN EN ISO 1421 |
| Tear resistance: | 360 / 290 N acc. DIN 53363 |
| Fire behaviour: | not easily flammable - B1 – acc. DIN 4102 |
| Standard roll width: | 762 / 1067 / 1372 / 1600 mm |
| Standard roll length: | 20 m |
| Temperature resistance: | -30 to 70 °C |
| Storage: | cool and dry environment, at 15-25 °C, 50 % rel. humidity |
| Shelf life: | 12 month in original packing |

COMPATIBLE INKS:

| | | | |
|--------------|-----|--------|-----|
| Eco solvent: | yes | UVC: | yes |
| Solvent: | yes | Latex: | yes |

Different printers, inks, resolutions and printing qualities result into numerous different printing parameters. In addition, there are numerous factors influencing processing and the application of our materials. For this reason, we cannot make specific statements as to drying times and maximum ink absorption. For this reason, we recommend you to perform own tests in order to verify the desired results. Our product specifications are not to be understood as legally binding guarantees assuring specific characteristics. Any liabilities and guarantees, as well as claims for compensation beyond the value of the product itself are excluded.

EMBLEM Solvent Banner Heavy Block Out 780 FR

Description:

EMBLEM Solvent Banner Block Out 780 FR with its grey basic fabric guarantees high opacity. Areas behind are covered perfectly. Prints from the back do not show through. With common solvent-, eco solvent-, latex- and UVC-inks you can print on both sides of our SOBBO780FR. As a cast banner it has an optimal flatness. Because of its resistance to weather and to UV-radiation it is versatilely applicable for middle- and long-term use. It corresponds to fire protection classification B1. So it can be used in interiors.

Processing:

SOBBO780FR can be eyed, welded, glued and sewed. When you use the banner outdoors please make sure that the distance of the grommets corresponds to the expected wind load and the weight of the material.

Application:

Production of promotion banners for in- and outdoor advertising, exhibition stand construction, displays at POS.