

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Version	Revision Date:	Date of last issue: -	GB:IE:MT / EN
1.0	20.01.2021	Date of first issue: 20.01.2021	

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier	: INK-3802
Trade name	: VJ-MS31 CYAN

1.2 Relevant identified uses of the substance or mixture and uses advised against Use of the Substance/ Mixture : Digital Printing

1.3 Details of the supplier of the safety data sheet

Company	: MUTOH Europe nv Archimedesstraat 13, 8400 Oostende, Belgium
Telephone	: +32 (0) 59 56 14 00
E-mail address	: sds@mutoh.eu

1.4 Emergency telephone number

+32 (0) 59 56 14 00 During normal opening times

Further information obtainable : sds@mutoh.co.jp

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Skin irritation, Category 2H315: Causes skin irritation.Eye irritation, Category 2H319: Causes serious eye irritation.Reproductive toxicity, Category 1BH360FD: May damage fertility. May damage the unborn child.

2.2 Label elements

from

Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms



Signal word	Danger	
Hazard statements	H315 Causes skin irritation.H319 Causes serious eye irritation.H360FD May damage fertility. May damage the	ne unborn child.
Precautionary statements	Prevention: P201 Obtain special instructions before use. P264 Wash skin thoroughly after handling. P280 Wear protective gloves/ protective clothi protection.	ng/ eye protec-tion/ face
	Response:	

P308 + P313 IF exposed or concerned: Get medical advice/ attention. P332 + P313 If skin irritation occurs: Get medical advice/ attention. P337 + P313 If eye irritation persists: Get medical advice/ attention.



Hazardous components which must be listed on the label: bis(2-(2-methoxy)ethyl)ether

Additional Labelling: Restricted to professional users.

2.3 Other hazards

Vapours may form explosive mixture with air.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Hazardous components

Chemical name	CAS-No.	Classification	Concentration
	EC-No.		(% w/w)
	Registration number		· · · ·
Bis(2-ethoxyethyl) ether	112-36-7	Skin Irrit. 2; H315	>= 20 - < 30
	203-963-7		
bis(2-(2-methoxyethoxy)ethyl)ether	143-24-8	Repr. 1B; H360FD	>= 10 - < 20
	205-594-7		
Propylene carbonate	108-32-7	Eye Irrit. 2; H319	>= 1 - < 10
	203-572-1		
	607-194-00-1		
Gamma-Butyrolactone	96-48-0	Acute Tox. 4; H302	>= 1 - < 3
	202-509-5	Eye Dam. 1; H318	
		STOT SE 3; H336	

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures	
General advice :	In the case of accident or if you feel unwell, seek medical advice immediately. When symptoms persist or in all cases of doubt seek medical advice.
Protection of first-aiders :	First Aid responders should pay attention to self-protection, and use the recommended personal protective equipment when the potential for exposure exists.
If inhaled :	If inhaled, remove to fresh air. Get medical attention.
In case of skin contact :	In case of contact, immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. Get medical attention. Wash clothing before reuse. Thoroughly clean shoes before reuse.
In case of eye contact :	In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. If easy to do, remove contact lens, if worn. Get medical attention.
If swallowed :	If swallowed, DO NOT induce vomiting. Get medical attention. Rinse mouth thoroughly with water.
4.2 Most important symptoms and effe	ects, both acute and delayed

Risks : Causes skin irritation. Causes serious eye irritation.



May damage fertility. May damage the unborn child.

4.3 Indication of any immediate medical attention and special treatment needed

: Treat symptomatically and supportively.

SECTION 5: Firefighting measures

Treatment

5.1 Extinguishing media Suitable extinguishing media Water spray Alcohol-resistant foam Carbon dioxide (CO2) Dry chemical Unsuitable extinguishing media : High volume water jet 5.2 Special hazards arising from the substance or mixture Specific hazards during : Do not use a solid water stream as it may scatter and spread firefighting fire. Flash back possible over considerable distance. Vapours may form explosive mixtures with air. Exposure to combustion products may be a hazard to health. Hazardous combustion products : Carbon oxides Nitrogen oxides (NOx) Metal oxides 5.3 Advice for firefighters Special protective equipment : In the event of fire, wear self-contained breathing apparatus. for firefighters Use personal protective equipment. Specific extinguishing methods : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment. Use water spray to cool unopened containers. Remove undamaged containers from fire area if it is safe to do so. Evacuate area.

SECTION 6: Accidental release measures

6.1 Personal precautions, protect	tive e	equipment and emergency procedures
Personal precautions	:	Remove all sources of ignition. Use personal protective equipment. Follow safe handling advice and personal protective equipment recommendations.
6.2 Environmental precautions		
Environmental precautions	:	Discharge into the environment must be avoided. Prevent further leakage or spillage if safe to do so. Prevent spreading over a wide area (e.g. by containment or oil barriers). Retain and dispose of contaminated wash water. Local authorities should be advised if significant spillages cannot be contained.
6.3 Methods and material for con-	tainr	ment and cleaning up
Methods for cleaning up	:	Non-sparking tools should be used. Soak up with inert absorbent material. Suppress (knock down) gases/vapours/mists with a water spray jet.

For large spills, provide dyking or other appropriate containment to keep material from spreading. If dyked material can be pumped, store recovered material in appropriate container. Clean up remaining materials from spill with suitable absorbent. Local or national regulations may apply to releases and disposal of

3/17



this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which regulations are applicable.

Sections 13 and 15 of this SDS provide information regarding certain local or national requirements.

6.4 Reference to other sections

See sections: 7, 8, 11, 12 and 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling Technical measures	:	See Engineering measures under EXPOSURE CONTROLS/ PERSONAL PROTECTION section.
Local/Total ventilation	:	Use with local exhaust ventilation.
Advice on safe handling	:	Do not get on skin or clothing. Do not breathe vapours or spray mist. Do not swallow. Do not get in eyes. Handle in accordance with good industrial hygiene and safety practice, based on the results of the workplace exposure as- sessment Keep container tightly closed. Keep away from heat and sources of ignition. Take precautionary measures against static discharges. Take care to prevent spills, waste and minimize release to the environment.
Hygiene measures	:	Ensure that eye flushing systems and safety showers are located close to the working place. When using do not eat, drink or smoke. Wash contaminated clothing before re-use.
7.2 Conditions for safe storage, incl	lud	ing any incompatibilities
Requirements for storage areas and containers		Keep in properly labelled containers. Store locked up. Keep tightly closed. Keep in a cool, well-ventilated place. Store in accordance with the particular national regulations. Keep away from heat and sources of ignition.
Advice on common storage	:	Do not store with the following product types: Strong oxidizing agents Organic peroxides Explosives Gases
7.3Specific end use(s)		
Specific use(s)	:	No data available
	,	

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

8.1.1 Occupational Exposure Limits

8.1.1.1 Great Britain

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
Pigment Blue	147-14-8	TWA (Dusts and mists)	1 mg/m3	GB EH40
15			(Copper)	
		STEL (Dusts and mists)	2 mg/m3	GB EH40
			(Copper)	



Contains no substances with occupational exposure limit values.

8.1.2 Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

Substance name	End Use	Exposure routes	Potential health effects	Value
Bis(2-ethoxyethyl) ether	Workers	Inhalation	Long-term systemic effects	50.5 mg/m3
	Workers	Skin contact	Long-term systemic effects	3.43 mg/kg bw/day
	Consumers	Inhalation	Long-term systemic effects	5.96 mg/m3
	Consumers	Skin contact	Long-term systemic effects	1.71 mg/kg bw/day
	Consumers	Ingestion	Long-term systemic effects	1.71 mg/kg bw/day
bis(2-(2- methoxyethoxy)ethyl)ether	Workers	Inhalation	Long-term systemic effects	22 mg/m3
	Workers	Skin contact	Long-term systemic effects	3 mg/kg bw/day
	Consumers	Inhalation	Long-term systemic effects	0.5 µg/m3
	Consumers	Skin contact	Long-term systemic effects	0.001 mg/kg bw/day
	Consumers	Ingestion	Long-term systemic effects	0.001 mg/kg bw/day
Propylene carbonate	Workers	Inhalation	Long-term systemic effects	176 mg/m3
	Workers	Inhalation	Long-term local ef-fects	20 mg/m3
	Workers	Skin contact	Long-term systemic effects	50 mg/kg bw/day
	Consumers	Skin contact	Long-term systemic effects	25 mg/kg bw/day
	Consumers	Inhalation	Long-term local ef-fects	10 mg/m3
	Consumers	Inhalation	Long-term systemic effects	43.5 mg/m3
	Consumers	Ingestion	Long-term systemic effects	25 mg/kg bw/day
Gamma-Butyrolactone	Workers	Inhalation	Long-term systemic effects	130 mg/m3
	Workers	Inhalation	Acute systemic ef-fects	958 mg/m3
	Workers	Skin contact	Long-term systemic effects	19 mg/kg bw/day
	Consumers	Inhalation	Long-term systemic effects	28 mg/m3
	Consumers	Inhalation	Acute systemic ef-fects	340 mg/m3
	Consumers	Skin contact	Long-term systemic effects	8 mg/kg bw/day
	Consumers	Ingestion	Long-term systemic effects	8 mg/kg bw/day
Pigment Blue 15	Workers	Inhalation	Long-term systemic effects	4 mg/m3
	Workers	Skin contact	Long-term systemic effects	450 mg/kg bw/day
	Consumers	Skin contact	Long-term systemic effects	225 mg/kg bw/day
	Consumers	Ingestion	Long-term systemic effects	45 mg/kg bw/day

8.1.3 Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006: Substance name Environmental Compartment Value



bis(2-(2- methoxyethoxy)ethyl)ether	Fresh water	32 mg/l
	Freshwater - intermittent	50 mg/l
	Marine water	3.2 mg/l
	Sewage treatment plant	500 mg/l
	Fresh water sediment	127 mg/kg dry weight (d.w.)
	Marine sediment	12.7 mg/kg dry weight (d.w.)
	Soil	6.7 mg/kg dry weight (d.w.)
	Oral (Secondary Poisoning)	8.32 mg/kg food
Propylene carbonate	Sewage treatment plant	7400 mg/l
	Fresh water	0.9 mg/l
	Marine water	0.09 mg/l
	Intermittent use/release	9 mg/l
	Soil	0.81 mg/kg
Gamma-Butyrolactone	Fresh water	0.056 mg/l
	Marine water	0.0056 mg/l
	Intermittent use/release	0.56 mg/l
	Sewage treatment plant	452 mg/l
	Fresh water sediment	0.24 mg/kg
	Marine sediment	0.02 mg/kg
	Soil	0.0147 mg/kg
Pigment Blue 15	Fresh water sediment	10 mg/kg
	Marine sediment	1 mg/kg
	Soil	1 mg/kg

8.2 Exposure controls

Engineering measures

Minimize workplace exposure concentrations. Use with local exhaust ventilation.

Personal protective equipment

Eye protection	Wear the following personal protective equipment: Safety goggles
Hand protection Material	Chemical-resistant gloves
Remarks	Choose gloves to protect hands against chemicals depending on the concentration and quantity of the hazardous substance and specific to place of work. Breakthrough time is not determined for the product. Change gloves often! For special applications, we recommend clarifying the resistance to chemicals of the aforementioned protective gloves with the glove manufacturer. Take note that the product is flammable, which may impact the selection of hand protection. Wash hands before breaks and at the end of workday.
Skin and body protection	Select appropriate protective clothing based on chemical resistance data and an assessment of the local exposure potential. Wear the following personal protective equipment: Flame retardant antistatic protective clothing, unless assessment demonstrates that the risk of explosive atmospheres or flash fires is low Skin contact must be avoided by using impervious protective clothing (gloves, aprons, boots, etc).
Respiratory protection	Use respiratory protection unless adequate local exhaust ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines.
Filter type	Combined particulates and organic vapour type (A-P)

MUTOH

9.1 Information on basic physical and chemical properties

3.1	Physical state	:	liquid
	Colour	:	cyan
	Odour	:	slight
	Odour Threshold	:	No data available
	Melting point/freezing point	:	No data available
	Boiling point or initial boiling point and boiling range	:	No data available
	Flammability	:	Not applicable
	Upper explosion limit	:	No data available
	Lower explosion limit	:	No data available
	Flash point	:	>= 70 °C Method: Seta closed cup
	Auto-ignition temperature	:	No data available
	Decomposition temperature	:	The substance or mixture is not classified self-reactive.
	рН	:	No data available
	Kinematic viscosity	:	No data available
	Solubility Water solubility	:	soluble
	Solubility in other solvents	:	soluble Solvent: organic solvents
	Partition coefficient: n-octanol/water	:	Not applicable
	Vapour pressure	:	No data available
	Density	:	0.9 - 1.1 g/cm3
	Relative vapour density	:	No data available
	Particle characteristics	:	Not applicable
9.2	Other information Evaporation rate	:	No data available
	Explosive properties	:	Not explosive
	Oxidizing properties	:	The substance or mixture is not classified as oxidizing.

SECTION 10: Stability and reactivity

10.1 Reactivity

Not classified as a reactivity hazard.

10.2 Chemical stability



Stable under normal conditions.

10.3 Possibility of hazardous rea Hazardous reactions	 Combustible liquid. Vapours may form explosive mixture with air. Can react with strong oxidizing agents.
10.4 Conditions to avoid Conditions to avoid	: Heat, flames and sparks.
10.5 Incompatible materials Materials to avoid	: Oxidizing agents
10.6 Hazardous decomposition No hazardous decomposition	
SECTION 11: Toxicological ir	nformation
11.1 Information on hazard class Information on likely routes of exposure	ses as defined in Regulation (EC) No 1272/2008 i Inhalation Skin contact Ingestion Eye contact
Acute toxicity Not classified based on availa	able information.
Product: Acute oral toxicity	: Acute toxicity estimate: > 2,000 mg/kg Method: Calculation method
Components: Bis(2-ethoxyethyl) ether: Acute oral toxicity	: LD50 (Rat): 4,970 mg/kg
bis(2-(2-methoxyethoxy)eth	
Acute oral toxicity	: LD50 (Rat): 3,850 mg/kg
Acute inhalation toxicity	 LC50 (Rat): > 11 mg/l Exposure time: 7 h Test atmosphere: vapour Method: OECD Test Guideline 403 Remarks: Based on data from similar materials
Acute dermal toxicity	: LD50 (Rat): > 5,000 mg/kg Remarks: Based on data from similar materials
Propylene carbonate: Acute oral toxicity	: LD50 (Rat): > 5,000 mg/kg
Acute dermal toxicity	: LD50 (Rabbit): > 2,000 mg/kg Assessment: The substance or mixture has no acute dermal toxicity
Gamma-Butyrolactone: Acute oral toxicity	: LD50 (Rat): 1,582 mg/kg
Acute inhalation toxicity	: LC50 (Rat): > 5.1 mg/l Exposure time: 4 h Test atmosphere: dust/mist

Causes skin irritation.



<u>Components:</u> Bis(2-ethoxyethyl) ether: Result Remarks	: Skin irritation : Based on data from similar materials
bis(2-(2-methoxyethoxy)ethyl) Species Method	ether: Rabbit OECD Test Guideline 404 No skin irritation
Result Propylene carbonate: Species Result	: Rabbit : No skin irritation
Gamma-Butyrolactone: Species Result	: Rabbit : No skin irritation
Serious eye damage/eye irrita Causes serious eye irritation.	ition
<u>Components:</u> Bis(2-ethoxyethyl) ether: Species Method Result	 Rabbit OECD Test Guideline 405 No eye irritation
bis(2-(2-methoxyethoxy)ethyl) Species Method Result)ether: : Rabbit : OECD Test Guideline 405 : No eye irritation
Propylene carbonate: Species Method Result	 Rabbit OECD Test Guideline 405 Irritation to eyes, reversing within 21 days
Gamma-Butyrolactone: Species Method Result	 Rabbit OECD Test Guideline 405 Irreversible effects on the eye
Respiratory or skin sensitisat	ion
Skin sensitisation Not classified based on available	e information.
Respiratory sensitisation Not classified based on available	e information.
Components: Bis(2-ethoxyethyl) ether: Test Type Exposure routes Species Method Result Remarks	 Local lymph node assay (LLNA) Skin contact Mouse OECD Test Guideline 429 negative Based on data from similar materials
bis(2-(2-methoxyethoxy)ethyl) Test Type)ether: : Local lymph node assay (LLNA)



Exposure routes

Exposure routes	: Skin contact
Species	: Mouse
Method	: OECD Test Guideline 429
Result	: negative
Remarks	: Based on data from similar materials
Gamma-Butyrolactone:	
Test Type	: Local lymph node assay (LLNA)
Exposure routes	: Skin contact
Species	: Mouse
Method	: OECD Test Guideline 429
Result	: negative
Germ cell mutagenicity Not classified based on availal	ble information.
<u>Components:</u> Bis(2-ethoxyethyl) ether:	
Genotoxicity in vitro	: Test Type: Bacterial reverse mutation assay (AMES) Result: negative
	Remarks: Based on data from similar materials
	Test Type: Chromosome aberration test in vitro
	Result: negative
	Remarks: Based on data from similar materials
	Test Type: In vitro mammalian cell gene mutation test
	Result: negative
	Remarks: Based on data from similar materials
Genotoxicity in vivo	: Test Type: Mutagenicity (in vivo mammalian bone-marrow cytogenetic
	test, chromosomal analysis)
	Species: Mouse
	Application Route: Ingestion
	Result: negative
	Remarks: Based on data from similar materials
	Nath an
bis(2-(2-methoxyethoxy)ethy	
Genotoxicity in vitro	: Test Type: Bacterial reverse mutation assay (AMES)
	Result: negative
	Test Type: In vitro mammalian cell gene mutation test
	Result: negative
	Test Type: In vitro sister chromatid exchange assay in mammalian
	cells
	Result: positive
Genotoxicity in vivo	· Test Type: Mutagenicity (in vive mammalian hone marrow extegenetic
Genoloxicity in vivo	: Test Type: Mutagenicity (in vivo mammalian bone-marrow cytogenetic test, chromosomal analysis)
	Species: Rat
	Application Route: inhalation (vapour)
	Result: negative
	Remarks: Based on data from similar materials
Propylene carbonate:	
Genotoxicity in vitro	: Test Type: Bacterial reverse mutation assay (AMES)
	Result: negative
Constaviaity in vive	Toot Type: Mammalian anthroasta miaronyalaya toot /in since
Genotoxicity in vivo	: Test Type: Mammalian erythrocyte micronucleus test (in vivo
	cytogenetic assay)
	cytogenetic assay) Species: Mouse
	cytogenetic assay)
	cytogenetic assay) Species: Mouse

: Skin contact



Result: negative

Gamma-Butyrolactone:

-	est Type: Bacterial reverse mutation assay (AMES) esult: negative
---	---

Carcinogenicity

Not classified based on available information.

Components: Pronylene carbonate:

Propylene carbonate:		
Species	:	Mouse
Application Route	:	Skin contact
Exposure time	:	2 Years
Result	:	negative
Gamma-Butyrolactone:		
Species		Rat

Species	:	Rat
Application Route	:	Ingestion
Exposure time	:	103 weeks
Result	:	negative

Reproductive toxicity

May damage fertility. May damage the unborn child.

Components:

Bis(2-ethoxyethyl) ether:	
Effects on fertility :	Test Type: One-generation reproduction toxicity study Species: Rat Application Route: Ingestion
	Result: negative
	Remarks: Based on data from similar materials
Effects on foetal develop- : ment	Test Type: Embryo-foetal development Species: Rabbit
ment	Application Route: Ingestion
	Result: negative
bis(2-(2-methoxyethoxy)ethyl)eth	ner:
Effects on fertility :	Test Type: Reproduction/Developmental toxicity screening test Species: Rat
	Application Route: Ingestion
	Method: OECD Test Guideline 421 Result: positive
Effects on foetal develop- :	Test Type: Embryo-foetal development
ment	Species: Rat
	Application Route: inhalation (vapour)
	Method: OECD Test Guideline 414 Result: positive
	Remarks: Based on data from similar materials
	Test Type: Embryo-foetal development
	Species: Rabbit Application Route: Ingestion
	Method: OECD Test Guideline 414
	Result: positive
	Remarks: Based on data from similar materials
	Test Type: Embryo-foetal development Species: Mouse

Application Route: Ingestion



	Result: positive Remarks: Based on data from similar materials
Reproductive toxicity - As- : sessment	Clear evidence of adverse effects on development, based on animal experiments., Clear evidence of adverse effects on sexual function and fertility, based on animal experiments.
Propylene carbonate: Effects on foetal develop : -ment	Test Type: Embryo-foetal development Species: Rat, female Application Route: Ingestion Result: negative
Gamma-Butyrolactone: Effects on fertility :	Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test Species: Rat Application Route: Ingestion Method: OECD Test Guideline 422 Result: negative Remarks: Based on data from similar materials
Effects on foetal develop- : ment	Test Type: Embryo-foetal development Species: Rat Application Route: Ingestion Result: negative
STOT - single exposure Not classified based on available ir	nformation.

Components:

Gamma-Butyrolactone:		
Assessment	:	May cause drowsiness or dizziness.

STOT - repeated exposure Not classified based on available information.

Components:

Components:	
bis(2-(2-methoxyethoxy)ethyl)e	
Assessment	No significant health effects observed in animals at concentra-tions of 100 mg/kg bw or less.
Repeated dose toxicity	
<u>Components:</u> Bis(2-ethoxyethyl) ether:	
Species	Rat
NOAEL	2.49 mg/l
Application Route	inhalation (dust/mist/fume)
	4 Weeks
Method	OECD Test Guideline 412
bis(2-(2-methoxyethoxy)ethyl)e	ther:
Species	Rat
NOAEL	250 mg/kg
Application Route	Ingestion
Exposure time	28 Days
Method	OECD Test Guideline 407
Remarks	Based on data from similar materials
Propylene carbonate:	
Species	Rat



NOAEL Application Route Exposure time	:	> 5,000 mg/kg Ingestion 90 Days	
Gamma-Butyrolactone:			
Species	:	Rat	
NOAEL	:	225 mg/kg	
Application Route	:	Ingestion	
Exposure time	:	13 Weeks	
Aspiration toxicity Not classified based on available information.			

11.2 Information on toxicological effects Endocrine disrupting properties : No data available

Other information :	:	No data available
---------------------	---	-------------------

SECTION 12: Ecological information

12.1 Toxicity

<u>Components:</u> Bis(2-ethoxyethyl) ether:		
Toxicity to fish	:	LC50 : > 10,000 mg/l Exposure time: 96 h
Toxicity to daphnia and other aquatic invertebrates	:	LC50 : 6,600 mg/l Exposure time: 96 h
Toxicity to microorganisms	:	NOEC : > 1,000 mg/l Exposure time: 3 h Method: OECD Test Guideline 209
Toxicity to daphnia and other aquatic invertebrates (Chron- ic toxicity)	:	EC10: > 1 mg/l Exposure time: 7 d Species: Ceriodaphnia dubia (water flea) Remarks: Based on data from similar materials
bis(2-(2-methoxyethoxy)ethy Toxicity to fish	l)etl :	her: LC50 (Danio rerio (zebra fish)): > 100 mg/l Exposure time: 96 h Method: OECD Test Guideline 203 Remarks: Based on data from similar materials
Toxicity to daphnia and other aquatic invertebrates	:	EC50 (Daphnia magna (Water flea)): 7,467 mg/l Exposure time: 48 h Method: OECD Test Guideline 202
Toxicity to algae	:	ErC50 (Pseudokirchneriella subcapitata (green algae)): 8,996 mg/l Exposure time: 72 h Method: OECD Test Guideline 201
		EC10 (Pseudokirchneriella subcapitata (green algae)): 2,871 mg/l Exposure time: 72 h Method: OECD Test Guideline 201
Toxicity to microorganisms	:	EC10 : > 100 mg/l Exposure time: 3 h Method: OECD Test Guideline 209 Remarks: Based on data from similar materials



Toxicity to daphnia and other aquatic invertebrates (Chron- ic toxicity)	:	NOEC: > 100 mg/l Exposure time: 21 d Species: Daphnia magna (Water flea) Method: OECD Test Guideline 211 Remarks: Based on data from similar materials		
Propylene carbonate: Toxicity to fish	:	LC50 (Cyprinus carpio (Carp)): > 1,000 mg/l Exposure time: 96 h		
Toxicity to daphnia and other aquatic invertebrates	:	EC50 (Daphnia magna (Water flea)): > 1,000 mg/l Exposure time: 48 h		
Toxicity to algae	:	ErC50 (Desmodesmus subspicatus (green algae)): > 900 mg/l Exposure time: 72 h		
Toxicity to microorganisms	:	EC50 (Pseudomonas putida): 25,619 mg/l Exposure time: 16 h		
Gamma-Butyrolactone: Toxicity to fish	:	LC50 (Lepomis macrochirus (Bluegill sunfish)): 56 mg/l Exposure time: 96 h		
Toxicity to daphnia and other aquatic invertebrates	:	EC50 (Daphnia magna (Water flea)): > 500 mg/l Exposure time: 48 h		
Toxicity to algae	:	EC50 (Desmodesmus subspicatus (green algae)): > 500 mg/l Exposure time: 72 h		
		NOEC (Desmodesmus subspicatus (green algae)): 31.25 mg/l Exposure time: 72 h		
Toxicity to microorganisms	:	IC50 : 4,518 mg/l Exposure time: 40 h		
12.2 Persistence and degradabilit	y			
<u>Components:</u> Bis(2-ethoxyethyl) ether: Biodegradability	:	Result: Not readily biodegradable. Biodegradation: 0 % Exposure time: 28 d Method: OECD Test Guideline 301F		
bis(2-(2-methoxyethoxy)ethyl)ether:				
Biodegradability	:	Result: Inherently biodegradable. Method: OECD Test Guideline 302B Remarks: Based on data from similar materials		
Propylene carbonate: Biodegradability	:	Result: Readily biodegradable. Biodegradation: 87.7 % Exposure time: 29 d Method: OECD Test Guideline 301B		
Gamma-Butyrolactone: Biodegradability	:	Result: Readily biodegradable. Biodegradation: 77 % Exposure time: 14 d Method: OECD Test Guideline 301C		
12.3 Bioaccumulative potential				



Components:

Bis(2-ethoxyethyl) ether:			
Partition coefficient: n- octanol/water	: log Pow: 0.39		
his (2-(2-methoxyethoxy)ethyl)ether:			

Partition coefficient: n- : log Pow: -0.84

		0001	
oct	tanol/v	vater	

Propylene carbonate:

Partition coefficient: n-	:	log Pow: -0.41
octanol/water		

Gamma-Butyrolactone:

Partition coefficient: n-	:	log Pow: -0.566
octanol/water		

12.4 Mobility in soil

No data available

- 12.5 Results of PBT and vPvB assessment Not relevant
- **12.6 Endocrine disrupting properties** No data available
- 12.7 Other adverse effects No data available

SECTION 13: Disposal considerations

13.1 Waste treatment methods Product Dispose of in accordance with local regulations. According to the European Waste Catalogue, Waste Codes are not product specific, but application specific. Waste codes should be assigned by the user, preferably in discussion with the waste disposal authorities. Contaminated packaging : Empty containers should be taken to an approved waste handling site for recycling or disposal. Empty containers retain residue and can be dangerous. Do not pressurize, cut, weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks, or other sources of ignition. They may explode and cause injury and/or death. If not otherwise specified: Dispose of as unused product.

Waste Code : 08 03 12, waste ink containing hazardous substances

SECTION 14: Transport information

14.1 UN number or ID number

Not regulated as dangerous goods

14.2 UN proper shipping name

Not regulated as dangerous goods

14.3 Transport hazard class(es) Not regulated as dangerous goods

14.4 Packing group



Not regulated as dangerous goods

14.5 Environmental hazards

Not regulated as dangerous goods

- **14.6 Special precautions for user** Not applicable
- **14.7 Maritime transport in bulk according to IMO instruments** Remarks : Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislati REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59).	on specific for the substance or mixture : bis(2-(2-methoxyethoxy)ethyl)ether
REACH - List of substances subject to authorisation (Annex XIV)	: Not applicable
Regulation (EC) No 1005/2009 on substances that deplete the ozone layer	: Not applicable
Regulation (EC) No 850/2004 on persistent organic pol- lutants	: Not applicable
Regulation (EC) No 649/2012 of the European Parlia- ment and the Council concerning the export and import of dangerous chemicals	: Not applicable
REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, preparations and articles (Annex XVII)	: Conditions of restriction for the fol- lowing entries should be considered: Number on list 3

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of majoraccident hazards involving dangerous substances. Not applicable

Other regulations:

Take note of Directive 92/85/EEC regarding maternity protection or stricter national regulations, where applicable.

Take note of Directive 94/33/EC on the protection of young people at work or stricter national regulations, where applicable.

15.2 Chemical safety assessment

A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

Other information	: Items where changes have been made to the previous version are highlighted in the body of this document by two vertical lines.
Full text of H-Statements	
H302	: Harmful if swallowed.
H315	: Causes skin irritation.
H318	: Causes serious eye damage.
H319	: Causes serious eye irritation.
H336	: May cause drowsiness or dizziness.
H360FD	: May damage fertility. May damage the unborn child.

Full text of other abbreviations



Acute Tox. Acute toxicity : Eve Dam. Serious eye damage Eve Irrit. Eve irritation : Repr. Reproductive toxicity Skin Irrit. Skin irritation STOT SE Specific target organ toxicity - single exposure GB EH40 UK. EH40 WEL - Workplace Exposure Limits GB EH40 / TWA Long-term exposure limit (8-hour TWA reference period) Short-term exposure limit (15-minute reference period) GB EH40 / STEL : Ireland. List of Chemical Agents and Occupational Exposure IE OEL Limit Values - Schedule 1 IE OEL / OELV - 8 hrs (TWA)

: Occupational exposure limit value (8-hour reference period)

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road; AICS -Australian Inventory of Chemical Substances; ASTM - American Society for the Testing of Materials; bw -Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR -Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx -Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB -Very Persistent and Very Bioaccumulative

Further information

Sources of key data used to Internal technical data, data from raw material SDSs, OECD eChem : compile the Safety Data Sheet Portal search results and European Chemicals Agency, http://echa.europa.eu/

Classification of the mixture:		Classification procedure:
Skin Irrit. 2	H315	Calculation method
Eye Irrit. 2	H319	Calculation method
Repr. 1B	H360FD	Calculation method

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.