

EMBLEM Solvent Universal Decoration Media

EMBLEM Solvent Universal Decoration Media is based on a non-woven polyester. It has a smooth canvas like surface and is printable with common eco solvent, solvent, latex and UVC inks. Due to its low weight and good flatness, paired with its high tensile resistance, non-woven polyester is suitable for multiple applications.

Matchcode:	SOUDM
Material:	non-woven polyester
Finish:	semi matt
Color:	white
Weight:	210 g/m ²
Thickness:	310 µm
Whiteness:	105 acc. ASTM D1925
Application temperature:	> +15 °C
Standard rolls width:	914 / 1524 mm
Standard roll length:	30 m
Storage:	cool and dry at 15-25 °C, 50 % rel. humidity
Shelf life:	12 months in original packing

COMPATIBLE INKS:

Eco Solvent:	yes	UVC:	yes
Solvent:	yes	Latex:	yes

Different printers, inks, resolutions and printing qualities result into numerous different printing parameters. In addition, there a numerous factors influencing processing and the application of our materials. For this reason, we cannot make specific statements as to drying times and maximum ink absorption. For this reason, we recommend you to perform own tests in order to verify the desired results. Our product specifications are not to be understood as legally binding guarantees assuring specific characteristics. Any liabilities and guarantees, as well as claims for compensation beyond the value of the product itself are excluded.



Gutenbergstraße 15 · D-24558 Henstedt-Ulzburg · Telefon: +49 4193-9950 · Telefax: +49 4193-995220 E-Mail: info@dataplot.de · Internet: www.dataplot.de



EMBLEM Solvent Universal Decoration Media

Description:

EMBLEM Solvent Universal Decoration Media is based on a non-woven polyester with a canvas embossing. Color-intensive prints can be created on SOUDM with standard eco solvent, solvent, latex and UVC inks. Due to its low weight and good flatness, together with its high tensile resistance, non-woven polyester is suitable for multiple applications indoors. It can be used as a canvas replacement for wedge frameworks, as there is no stress-whitening in the coating and it features high scratch resistance. Additionally, SOUDM is PVC-free.

Processing:

Before further processing the VOC's of solvent, eco-solvent and latex inks must be dried completely. The drying time depends on the amount of ink.

Before printing check the correct drying temperature by carrying out a trial print. To avoid fingerprints the use of cotton gloves is advised.

Application:

Printing applications for SOUDM are stretcher frame, fine art, event banner, wallpaper, interior design, X-banner applications, roll-ups and ceiling pendants.