## **EMBLEM EASY PASTE II - 25835**



Professional ready to use adhesive, designed for heavy wallpapers. Manufactured from high-quality starch additives, and fungicides.

- big wet bond strength
- better positioning

Yield: 1 kg of adhesive on the surface of 5-6 m2.

## Recommended for wallpaper with a weight up to 450 g/m2:

- non woven wallpaper, textiles,
- wallpaper with non-woven backing,
- glass fiber

## Available in rectangular packages:

- 10kg

## Other technical information:

Composition	modified maize starch, PVA dispersion		
Form	paste		
Temperature of application	from 18 to 25 ℃		
Preparation	-after opening the container the glue mix until homogenous - heavy wallpaper glue is not diluted - apply glue directly on the wall using a paint roller or brush  Remove the excess glue with a damp cloth or sponge.		
Full cure time	from 24 to 36 h		
Viscosity	40 000 +/- 5000 mPas		
PH value	6.5 +/- 0,5 at 20 ° C		
Metod of application	brush, roller		
Type of surface	plaster (gypsum, cement), ceramic plaster - cardboard		
Surface preparation	the surface should be smooth, dry, clean and free from old paint remain and grease. Wall defects (scratches, holles) must be repaired. New an absorbent wall should be sized prior to paper - hanging		
Storage conditions	indoor temperature: +5 to +35 °C, avoid freezing		
Package	tightly closed buckets		
Smell	characteristic of PVA		
Colours	milky-white		
Shelf life	minimum one year from date of manufacture on the packaging		