

EMBLEM TREND Billboard Paper Blueback II

EMBLEM TBB II is a matt, white, barrier coated paper for water based inks. Because of the high opacity, due to the blue back, it is an excellent media for poster applications for indoor- and outdoor use.

Matchcode:	TBB2
Material:	paper, water resistant, backside blue
Finish:	matt
Color:	white
Weight:	130 g/m ²
Opacity:	>98 %
Standard roll width:	24" / 36" / 42" / 50" / 54"
Standard roll length:	25 m
Flame retardant:	no
Storage:	at 15 - 25 °C, 50 % rel. humidity
Shelf life:	24 month in original boxes
Waterresistant (not Dye):	yes

COMPATIBLE INKS:

Dye:	yes
Pigment:	yes

Different printers, inks, resolutions and printing qualities result into numerous different printing parameters. In addition, there are numerous factors influencing processing and the application of our materials. For this reason, we cannot make specific statements as to drying times and maximum ink absorption. For this reason, we recommend you to perform own tests in order to verify the desired results. Our product specifications are not to be understood as legally binding guarantees assuring specific characteristics. Any liabilities and guarantees, as well as claims for compensation beyond the value of the product itself are excluded.

EMBLEM TREND Billboard Paper Blueback II

Description:

EMBLEM TBB2 is a matt, white, barrier coated paper for waterbased inks. Because of the high opacity, due to the blue back, it is an excellent media for poster applications for indoor- and outdoor use.

Water resistance is only achieved when using pigmented inks.

The specific surface permits a very good ink coverage and brilliant colors.

Processing:

When using TBB2 for billboards we recommend for an optimal bonding to paste the board and not the paper (e. g. with Henkel UST 2500N Zellura).

The paste must not contain any glycol or any solvents. Before mounting it is advised to soak the prints for about 15 minutes and a following processing within 24 to 72 hours. It is not commendable to inlay the paper in the paste.

In case of overlapping bonding these areas have to be provided with enough paste to reach the optimum adhesion. A loss of 1% lengthwise and in transverse direction has to be taken in account.

The optimum waterproofness will be achieved when the prints get a drying time of approximate 10 hours before processing.

To use the paper with other printers or inks, the usage of different pastes or other techniques of pasting may cause problems like smearing, fading or removing.

To avoid fingerprints the use of cotton gloves is advised.

Application:

Billboards

EMBLEM TREND Billboard Paper Blueback II

Procedure for assembly of this special InkJet-Posterpaper

Reports of experienced users have shown that this InkJet-Specialpaper is best assembled as follows:

1. Print the paper with printers and inks as indicated in the actual data sheets.
2. Store the prints 10-12 hours open to optimise the best efforts of water resistance.
3. Soak the prints in water for max. 15 minutes.
4. Wait for minimum of 24 hours to maximum 72 hours with the print in slightly wet storage, e. g. in a closed box. This is necessary for a maximum saturation of the paper. Do not soak the prints with glue!
5. To optimise the bonding, we recommend to use special glue for outside areas (e. g. Henkel UST 2500N Zellura or Bacoplak Bacocell) Put the glue to the underground not to the print. The glue has to be free of glycol and solvent.
6. If it is necessary to overlap prints, e.g. on 18/1 walls, it is useful to use on the overlapping part more glue to achieve a better contact. Also if you post a single print, it is required to get enough glue to the position of edges and sides of the print on the underground.

If possible, the time of gluing has to be planned to avoid direct solar radiation, which could cause that the print dries too quick, stripes from the underground and rolls itself up.

During the drying time there might be a shrinking of 1% in both directions.

DO NOT compare this special Ink Jet paper with normal poster papers to be used on other printing technologies. This Ink Jet paper has a different characteristic during the gluing process. Please notify your processor who will glue on this product in your own interest to get the optimal result.