

EMBLEM Solvent Value PopUp Film FR

EMBLEM SOVDFFR is a rigid PVC film with a satin coating for solvent-based inks. The high opacity allows the use in POP-ups. This film can be used indoors and outdoors.

Matchcode:	SOVDFFR
Material:	rigid PVC
Finish:	satin
Color:	white
Thickness:	360 μm
Visual density:	1,6
Fire behaviour:	not certified
Standard roll width:	914 / 1067 / 1270 mm
Standard roll length:	20 m
Storage:	cool and dry environment at 15-25 °C, 50 % rel. humidity
Shelf life:	up to 3 years in original packing

COMPATIBLE INKS:

Eco solvent:	yes	UVC:	yes
Solvent:	yes	Latex:	no

Different printers, inks, resolutions and printing qualities result into numerous different printing parameters. In addition, there a numerous factors influencing processing and the application of our materials. For this reason, we cannot make specific statements as to drying times and maximum ink absorption. For this reason, we recommend you to perform own tests in order to verify the desired results. Our product specifications are not to be understood as legally binding guarantees assuring specific characteristics. Any liabilities and guarantees, as well as claims for compensation beyond the value of the product itself are excluded.



Gutenbergstraße 15 · D-24558 Henstedt-Ulzburg · Telefon: +49 4193-9950 · Telefax: +49 4193-995220 E-Mail: info@dataplot.de · Internet: www.dataplot.de



EMBLEM Solvent Value PopUp Film FR

Description:

EMBLEM SOVDFFR is a rigid PVC film with a satin coating for solvent-based inks. The high opacity allows the use in POP-ups. This film can be used indoors and outdoors. This special film is for indoor and outdoor application like roll-ups, stand displays, poster, shop-decoration and exhibitions.

Processing:

The drying of the printed medium is highly dependent on the inks used as well as the solvent coating and the color saturation. When printing film in a roll-to-roll process, their printed strip should be unrolled and laid flat as soon as possible until final drying. Solvent residues due to insufficient drying times can lead to blocking during transport in rolled-up form.

During lamination such residues can negatively impact flatness, the shrinkage behaviour and the anchorage of the laminate on the printed film.

After printing we recommend to store the remaining roll in the closed original packing in a cool and dry environment.

We recommend to protect the printed surface if it is subject to abrasion, sweat or other mechanical influences. In this case we recommend to protect the image with laminating film. To avoid fingerprints the use of cotton gloves is advised.

Application:

pop-ups, displays, POS, poster, shop-decoration and exhibitions