

EMBLEM Trend Victory Vinyl

EMBLEM Trend Victory Vinyl is a matt white coated soft PVC film for printing with waterbased inks. Prints with high colour brilliance can be achieved on the low-reflection surface. SFOMPOXV can be used to create self-adhesive prints for indoor and outdoor use.

Matchcode:	SFOMPOXV
Material:	microporous coated PVC film, monomeric
Finish:	matt
Colour:	white
Thickness:	100 μ m (film)
Adhesive:	clear, permanent acrylic adhesive, solvent-free
Liner:	kraft liner siliconised, about 135 g/m ²
Adhesion power:	\geq 10 N / 25 mm acc. to FTM 1 - 24 h
Application temperature:	≥15 °C
Fire behaviour:	not easily flammable - class B1 for building materials - acc.
	DIN 4102-1 on metal surfaces
Lamination	cold
Standard roll width:	610 / 914 / 1067 / 1270 / 1372 / 1524 mm
Standard roll length:	30 m
Core diameter:	51 mm (2")
Durability:	up to 12 months with pigmented ink outdoors, unlaminated,
	under normal Central European climate
Storage:	cool and dry at 15-25 °C, 50 % rel. humidity
Shelf life:	12 month in original boxes

COMPATIBLE INKS:

Dye: yes Pigment: yes

Different printers, inks, resolutions and printing qualities result into numerous different printing parameters. In addition, there a numerous factors influencing processing and the application of our materials. For this reason, we cannot make specific statements as to drying times and maximum ink absorption. For this reason, we recommend you to perform own tests in order to verify the desired results. Our product specifications are not to be understood as legally binding guarantees assuring specific characteristics. Any liabilities and guarantees, as well as claims for compensation beyond the value of the product itself are excluded.



Gutenbergstraße 15 · D-24558 Henstedt-Ulzburg · Telefon: +49 41 93-99 50 · Telefax: +49 41 93-99 52 20 E-Mail: info@dataplot.de · Internet: www.dataplot.de



EMBLEM Trend Victory Vinyl

Description:

EMBLEM Trend Victory Vinyl is a matt white coated soft PVC film for printing with waterbased inks. The low-reflection surface is waterproof and universally printable. Prints with high colour brilliance can be achieved.

SFOMPOXV can be used to create self-adhesive prints for indoor and outdoor use. Water resistant prints can only be achieved with pigmented inks. Prints made with dye-based inks should be laminated to improve durability. Trend Victory Vinyl can be edge to edge laminated. It is used for short to medium term applications. The durability is strongly influenced by the environmental conditions, the location and the surface to be covered. Main indoor applications are stickers, posters, displays and trade fair construction. Outdoors, it is often used for signage, construction signs and shop window design.

Processing:

The print should be allowed to dry for at least 24 hours to avoid problems during further processing / lamination.

When using dye inks, the prints should always be protected against gas fading by lamination, even if used for a short time. The use of a laminate is recommended for protection against mechanical influences. Prints can be edge to edge laminated. With proper processing, moisture penetration of more than 3-5 mm is not to be expected.

Lamination should be done with a monomeric PVC film in cold process.

To avoid contamination of unprinted or light areas via water droplets running down, it is recommended to flush unlaminated prints with clean tap water prior to outdoor application. To avoid fingerprints, it is recommended to wear cotton gloves.

Application:

The main field of application is the production of self-adhesive prints for indoor and outdoor advertisements.