

EMBLEM Polypropylen Film Glossy 60 C P

EMBLEM Polypropylen Film Glossy 60 C P is a glossy coated, white polypropylene film, which can be printed with common latex and UVC inks. Due to the good UV stability the product can also be used outdoors. Typical applications are trade fair construction, POS and signs.

| | |
|----------------------------|---|
| Matchcode: | POPFIGL60CP |
| Material: | polypropylene |
| Finish: | glossy |
| Color: | white |
| Thickness: | 60 µm |
| Adhesive: | transparent, permanent, polyacrylate |
| Liner: | PE coated kraft paper, 130 g/m ² |
| Adhesion power - 24 hours: | 12 N/ 25 mm, acc. Finat 1 (average value) |
| Temperature resistance: | -10 °C to +80 °C |
| Application temperature: | more than 15 °C |
| Fire behaviour: | not tested |
| Standard rolls width: | 1067 / 1370 mm |
| Standard roll length: | 50 m |
| Durability: | up to 24 months in outdoor areas, vertically applied, under normal Central European climate |
| Storage: | cool and dry environment, at 15-25°C, 50% rel. humidity |
| Shelf life: | 12 month in original packing |

COMPATIBLE INKS:

| | | | |
|--------------|----|--------|-----|
| Eco Solvent: | no | UVC: | yes |
| Solvent: | no | Latex: | yes |

Different printers, inks, resolutions and printing qualities result into numerous different printing parameters. In addition, there are numerous factors influencing processing and the application of our materials. For this reason, we cannot make specific statements as to drying times and maximum ink absorption. For this reason, we recommend you to perform own tests in order to verify the desired results. Our product specifications are not to be understood as legally binding guarantees assuring specific characteristics. Any liabilities and guarantees, as well as claims for compensation beyond the value of the product itself are excluded.