

EMBLEM Solvent Paper 135 Adhesive

EMBLEM Solvent Paper 135 Adhesive is based on a wet-strength paper, which is self-adhesive. The paper can be processed in cutting plotters. It can be used for short-term outdoor applications. The SOPA135ADH is PVC free.

| | |
|--------------------------|--|
| Matchcode: | SOPA135ADH |
| Material: | paper |
| Finish: | semi glossy |
| Color: | white |
| Weight: | 135 g/m ² plus adhesive and liner - ISO 536 |
| Opacity: | 97 % - ISO 2471 |
| Adhesive: | water-based acrylic adhesive |
| Liner: | one-side siliconised kraft paper, 120 g/m ² |
| Adhesion (on glass): | 20 N/25 mm acc. FTM 1 - 24 h (average value) |
| Adhesive weight: | 20 g/m ² |
| Application temperature: | from 10 °C |
| Standard rolls width: | 762 / 1372 / 1524 mm |
| Standard roll length: | 30.5 m |
| Durability: | up to 3 months in outdoor areas, under Central European standard climate |
| Storage: | cool and dry environment, at 10-30 °C, 30-65 % rel. humidity |
| Shelf life: | 12 month in original packing |

COMPATIBLE INKS:

| | | | |
|--------------|-----|--------|-----|
| Eco Solvent: | yes | UVC: | yes |
| Solvent: | yes | Latex: | yes |

Different printers, inks, resolutions and printing qualities result into numerous different printing parameters. In addition, there are numerous factors influencing processing and the application of our materials. For this reason, we cannot make specific statements as to drying times and maximum ink absorption. For this reason, we recommend you to perform own tests in order to verify the desired results. Our product specifications are not to be understood as legally binding guarantees assuring specific characteristics. Any liabilities and guarantees, as well as claims for compensation beyond the value of the product itself are excluded.