

EMBLEM Latex-UV Wall Decoration 130 Adhesive

EMBLEM Latex UV Wall Decoration 130 Adhesive is a wallpaper based on non-woven paper for individual interior design. The matt, white surface of the wallpaper can be printed with standard latex and UV inks and is characterized by a soft feel. The back of the product is self-adhesive.

Matchcode:	LUVWADE130ADH
Material:	non-woven paper, free of glass fibre
Finish:	matt
Color:	white
Weight:	132 g/m ² ± 5 g/m ² - ISO 536
Thickness:	233 µm ± 8 µm - ISO 534
Opacity:	> 87 % - ISO 2469
CIE whiteness:	> 97 %, D65/10° - ISO 2469
Adhesive:	water-based acrylic adhesive, permanent
Liner:	glassine liner, 65 g/m ²
Adhesion power:	N/A, final adhesion is achieved after 16-24 hours
Adhesion weight:	40 g/m ²
Application temperature:	+20 °C - +25 °C
Fire behaviour:	N/A
Standard roll width:	762 / 1524 mm
Standard roll length:	50 m
Storage:	cool and dry environment, at 15-25 °C, 50 % rel. humidity
Shelf life:	12 months in original packing

COMPATIBLE INKS:

Eco solvent:	no	UVC:	yes
Solvent:	no	Latex:	yes
		Dry toner:	yes

Different printers, inks, resolutions and printing qualities result into numerous different printing parameters. In addition, there are numerous factors influencing processing and the application of our materials. For this reason, we cannot make specific statements as to drying times and maximum ink absorption. For this reason, we recommend you to perform own tests in order to verify the desired results. Our product specifications are not to be understood as legally binding guarantees assuring specific characteristics. Any liabilities and guarantees, as well as claims for compensation beyond the value of the product itself are excluded.

EMBLEM Latex-UV Wall Decoration 130 Adhesive

Description:

EMBLEM Latex UV Wall Decoration 130 Adhesive is a wallpaper based on non-woven paper for individual interior design. The matt, white surface of the wallpaper can be printed with standard latex and UV inks and is characterized by a soft feel. The back of the product is self-adhesive.

Due to the special surface you can achieve brilliant photorealistic prints with a high ink coverage. This product is free of PVC, plasticizers and solvents. Without the addition of heavy metal compounds and formaldehyde.

EMBLEM LUVWADE130ADH is stable in dimension, crack-bridging and easy to apply. The wallpaper adheres to smooth wall surfaces or plasters painted with dispersion paint or primer.

Processing:

The prints are suitable for indoor decoration without lamination.

The wallpaper should acclimatize sufficiently (up to 48 hours) before it is glued. The substrate should be as well prepared as for wallpapering with paste and should correspond to quality level 3. This means that the substrate must be dry, clean, firm, absorbent and smooth. If necessary, the substrate should be primed. Existing paints, plasters or fillers must be thoroughly dried. Please refer to the manufacturer's instructions for guidance.

Multiple panels are hung edge-to-edge. The wallpaper can still be repositioned within the first 10 minutes. Press on the strips with sponge rubber roller or wallpapering brush without bubbles.

Application:

Typical applications for EMBLEM LUVWADE130ADH are individual decoration for living spaces, children's rooms, shopping malls, museums, booth constructions, commercial buildings, hotels and restaurants, wall tattoos.