

EMBLEM Solvent Magic Grip Clear Neo

EMBLEM Solvent Magic Grip Clear Neo is based on a transparent polyester film. The back side of the film adheres on smooth surfaces because of micro suction technology. It is easy to apply and removeable without residue. Typical applications are short term promotions and interior designs.

Matchcode:	SOMAGRICLN
Material:	coated polyester film
Finish:	glossy
Color:	clear
Thickness:	110 μ m
Weight:	150 g/m ²
Liner:	PET film, translucent, 50 μ m
Application temperature:	> +10 °C
Standard roll width:	1372 mm
Standard roll length:	30 m
Durability:	short term indoor applications, up to 6 months
Storage:	cool and dry at 15-25 °C, 50 % rel. humidity
Shelf life:	12 months in original packing

COMPATIBLE INKS:

Eco Solvent:	yes	UVC:	yes
Solvent:	yes	Latex:	yes

Different printers, inks, resolutions and printing qualities result into numerous different printing parameters. In addition, there are numerous factors influencing processing and the application of our materials. For this reason, we cannot make specific statements as to drying times and maximum ink absorption. For this reason, we recommend you to perform own tests in order to verify the desired results. Our product specifications are not to be understood as legally binding guarantees assuring specific characteristics. Any liabilities and guarantees, as well as claims for compensation beyond the value of the product itself are excluded.

EMBLEM Solvent Magic Grip Clear Neo

Despriction:

EMBLEM Solvent Magic Grip Clear Neo which is based on a transparent polyester film with a glossy coating, is made for printing with common eco solvent, solvent, UVC and latex-based inks. Objects behind the film are not blurred because of its clearness. Innovative micro suction technology enables EMBLEM Solvent Magic Grip Clear Neo to easily adhere on smooth surfaces. It has a better UV stability because of an improved adhesive layer. With the thinner film it is easier to apply. You are still able to remove the film without residue.

Processing:

The film adheres only on smooth, flat or cylindrical surfaces like windows. The subsurfaces which are to be pasted up have to be free of dust and grease. The user is advised to make tests before application to check compatibility between film and subsurface. Please always keep the micro suction layer free of dust. If necessary clean the micro suction layer carefully with water.

To get bubble free adherence it is possible to spray the subsurface with clear water. After spraying it is advised too squeegee the surface to remove all of the water.

To avoid fingerprints the use of cotton gloves is advised.

Application:

Typical indoor-applications are short term promotions, shop window advertising and interior design.