

## EMBLEM Solvent Polypropylen Film Easy Tack

EMBLEM Solvent Polypropylene Film Easy Tack is a self-adhesive, tear-resistant polypropylene film for printing with common solvent, EcoSolvent and UV inks. The low-reflection coating enables waterproof prints with excellent colour reproduction. The Easy Tack adhesive allows residue-free removal from smooth surfaces.

Matchcode:	<b>SOPPET</b>
Material:	polypropylen
Finish:	satın
Color:	white
Whiteness CIE:	82, D65/2° acc. ISO 11476
Thickness:	170 µm
Adhesive:	transparent, removable, acrylate
Liner:	siliconized kraft paper, 135 g/m <sup>2</sup>
Adhesion power - 48 hours:	ca. 0,5 N/ 25 mm, on glass, acc. Finat 1 (average value)
Application temperature:	more than 15 °C
Standard rolls width:	914 mm
Standard roll length:	30 m
Durability:	up to 24 months in indoor areas, under Central European standard climate
Storage:	cool and dry environment, at 10-30 °C, 30-65 % rel. humidity
Shelf life:	12 month in original packing

### COMPATIBLE INKS:

Eco Solvent:	yes	UVC:	yes
Solvent:	yes	Latex:	no

Different printers, inks, resolutions and printing qualities result into numerous different printing parameters. In addition, there are numerous factors influencing processing and the application of our materials. For this reason, we cannot make specific statements as to drying times and maximum ink absorption. For this reason, we recommend you to perform own tests in order to verify the desired results. Our product specifications are not to be understood as legally binding guarantees assuring specific characteristics. Any liabilities and guarantees, as well as claims for compensation beyond the value of the product itself are excluded.

## EMBLEM Solvent Polypropylen Film Easy Tack

### Description:

EMBLEM Solvent Polypropylene Film Easy Tack is a self-adhesive, tear-resistant polypropylene film. The low reflective coating allows waterproof prints with excellent colour reproduction. The polypropylene can be printed with common eco-solvent, solvent and UV inks. The Easy Tack adhesive is designed for medium-term indoor use. It can be applied easily and without bubbles. It can be removed from smooth surfaces without leaving any residue. The tear-resistant polypropylene film is also suitable for further processing in cutting plotters. This product, produced in Europe, complies with EU Regulation 1907/2006 (REACH) and is PVC-free.

### Processing:

Prints containing volatile VOC's must be completely dry before further processing. The drying of the printed media is highly dependent on the ink coverage.

Additional surface protection is required if the print surface is exposed to moisture, abrasion, hand perspiration or other mechanical influences over a longer period of time. In this case, the print surface must be protected with self-adhesive laminating films or suitable liquid laminates. During lamination or mounting, solvent residues can also negatively influence the quality of the finished product (flatness, shrinkage, anchoring, adhesive strength, etc.).

Correct device and temperature settings should be checked by a test print.

The substrate to be applied must be thoroughly cleaned of dirt, dust, grease, etc.

To avoid fingerprints, the use of cotton gloves is recommended.

### Application:

Typical applications: Signage, POS advertising, seasonal advertising