

# EMBLEM Production Banner 440 Semi Matt II

EMBLEM PROBA440SM2 is a laminated PVC banner made to be used as a frontlit banner. It is based on a high quality polyester fabric with an even structure. The semi matt surface enables excellent color reproduction. The main use of this banner is short-term advertising indoors.

Matchcode:	PROBA440SM2	
Material:	PVC coated scrim	
Finish:	semi matt	
Color:	white	
Weight:	440 g/m <sup>2</sup> ±10	
Breaking strength:	635/450 N/5 cm acc. DIN 53352	
Tear strength:	65/45 N acc. DIN 53356	
Fire behaviour:	N/A	
Standard roll width:	760 / 1100 / 1370 / 1520 / 1600 mm	
Standard roll length:	25 m	
Temperature resistance:	-20 °C to +70 °C	
Storage:	cool and dry at 15-25 °C, 50 % rel. humidity	

#### **COMPATIBLE INKS:**

Eco solvent:	yes	UVC:	yes
Solvent:	yes	Latex:	yes

Different printers, inks, resolutions and printing qualities result into numerous different printing parameters. In addition, there a numerous factors influencing processing and the application of our materials. For this reason, we cannot make specific statements as to drying times and maximum ink absorption. For this reason, we recommend you to perform own tests in order to verify the desired results. Our product specifications are not to be understood as legally binding guarantees assuring specific characteristics. Any liabilities and guarantees, as well as claims for compensation beyond the value of the product itself are excluded.



Gutenbergstraße 15 · D-24558 Henstedt-Ulzburg · Telefon: +49 4193-9950 · Telefax: +49 4193-995220 E-Mail: info@dataplot.de · Internet: www.dataplot.de



# EMBLEM Production Banner 440 Semi Matt II

## Description:

EMBLEM PROBA440SM2 is a laminated PVC banner with a polyester fabric core. It has been developed to be used as a frontlit advertisement. The white, semi matt surface enables excellent color reproduction. The structure on the back prevents the banner of sticking together in a rolled-up state. PROBA440SM2 can be printed with common solvent, eco solvent, latex and UVC inks.

It can be used in many applications for short-term advertising.

### Processing:

The material can be eyed, welded is stickable and sewable. It is necessary that eyelets are placed in a distance which is proportionated to the expected wind load and own weight of the banner.

Please take care that the banner is fixed at the full width to the core caused for technical reasons.

### Application:

The main use of this banner is short-term advertising.