

EMBLEM Green Vision Maple

The Green Vision Maple emblem is a PVC-free banner for commercial use with a textile structure. The grey backing ensures perfect coverage of surfaces. The low weight makes EGV Maple the perfect choice for wall coverings in the contract business. The surface impresses with its low reflectivity.

Matchcode:	EGV-MAPLE
Material:	Polyester fabric, coated with grey backing, PVC free
Finish:	matt
Color:	white
Weight:	270 g/m ² ± 10 %
Tear strength:	1800 / 1200 N/5 cm nach ISO 1421
Tear resistance:	265 / 120 N/5 cm DIN 53363
Fire behaviour:	not easily flammable - B1 – acc. DIN 4102
Standard roll widths:	1060 / 1372 / 1600 mm, other widths on request Standard
roll length:	25 m
Storage:	cool and dry at 10-30 °C, 50 % relative humidity
Shelf life:	12 months in original packaging, stored horizontally

COMPATIBLE INKS:

Eco Solvent:	no	UV:	yes
Solvent:	no	Latex:	yes

Different printers, inks, resolutions and printing qualities result into numerous different printing parameters. In addition, there are numerous factors influencing processing and the application of our materials. For this reason, we cannot make specific statements as to drying times and maximum ink absorption. For this reason, we recommend you to perform own tests in order to verify the desired results. Our product specifications are not to be understood as legally binding guarantees assuring specific characteristics. Any liabilities and guarantees, as well as claims for compensation beyond the value of the product itself are excluded.

EMBLEM Green Vision Maple

Description:

The Green Vision Maple emblem is a PVC-free banner for commercial use with a textile structure. The grey reverse side enables high contact opacity. This means that the banner covers substrates very well. The textile structure of the surface reduces light reflections caused by lighting and has excellent colour rendering. It can be printed with commercially available solvent, eco-solvent, latex and UV inks. Due to these advantages and its low weight, Emblem Green Vision Maple is used for wall coverings and curtains in the contract business, displays, projection screens and as a canvas alternative.

Processing:

The material can be eyeleted, glued and sewn. For outdoor use, it must be ensured that the distance between the eyelets on oiled banners is based on the expected load, e.g. wind or dead weight. The volatile VOCs contained in solvent, eco-solvent and latex inks must be completely dried out before further processing. The ink application is decisive for the drying of the printed medium. Check the device and temperature settings by carrying out a test print. Use cotton gloves to avoid fingerprints. The usual procedures for wallpapering apply for further processing as decorative wallpaper. The surface must be smooth, firm and dry when you apply the wallpaper. Surface soiling such as grease, dirt etc. must be removed. All unevenness must be removed from the substrate in order to achieve optimum wallpapering results. For gluing EGV Maple, we recommend using dispersion adhesives that have been specially developed for this application. The customer must carry out their own tests for the respective combination of adhesive, substrate and decorative wallpaper.

Application:

Typical applications include wall coverings, curtains, displays, projection screens and screens in hotel chains, office buildings, schools, apartment blocks and other properties.