

EMBLEM EASY Tape Solid

EMBLEM EASY Tape Banner plus is a very strong sticking, double-sided adhesive tape. The adhesive based on acrylate dispersion. The adhesive indicates a high solvent, humidity and climatic stability when in use. Also it has an excellent stability against plasticiser.

EMBLEM EASY Tape Solid

Material:	double-sided adhesive tape
Carrier:	PVC film 80 µm white
Liner:	both sided siliconised liner, 90 g/m ²
Colour of Adhesion:	white
Weight of adhesion:	170 g/m ²
Total thickness:	250 μm
Adhesion:	modified polyacrylic, permanent
Peel adhesion on steel:	min. 35 N/25 mm
after 1h (acc. AFERA 5001)	
Appl. temperature:	> +10°C
Temperature resistance:	-40°C to +130°C
Width of roll:	15 mm, 40 mm
Length of roll:	25 m
Storage:	cool and dry, no direct sun exposure

There is a possibility of lateral leakage of glue caused by storing over recommended storage temperature. Thereby the adhesive property are not impaired. In order to avoid a sticking of the individual windings together, the roles should be flat stored on a siliconised paper. Mechanical effects must be avoided, since this can involve to sticking together of the winding.

Different printers, inks, resolutions and printing qualities result into numerous different printing parameters. In addition, there a numerous factors influencing processing and the application of our materials. For this reason, we cannot make specific statements as to drying times and maximum ink absorption. For this reason, we recommend you to perform own tests in order to verify the desired results. Our product specifications are not to be understood as legally binding guarantees assuring specific characteristics. Any liabilities and guarantees, as well as claims for compensation beyond the value of the product itself are excluded.



Gutenbergstraße 15 · D-24558 Henstedt-Ulzburg · phone: +49 4193-9950 · fax: +49 4193-995220 email: info@dataplot.de · internet: www.dataplot.de



EMBLEM EASY Tape Solid

Description:

EMBLEM EASY Tape Solid is a very strongly sticking, double-sided adhesive tape with high tack. The adhesive based on modified polyacrylate. The adhesive indicates a high humidity and climatic stability when in use.

The PVC carrier enables a high excellent adaptability to a wide varity of surfaces such as various plastics, glass, aluminium and other metals. There is a good adhesion to nonpolar surfaces such as PE and PP film.

Our tests showed that EMBLEM EASY Tape Solid is suitable for gluing most EMBLEM films. It can be used for gluing of heavy displays, rollups, several panels, etc. . Self-test are required when using the EASY Tape Textile with materials outside of the EMBLEM-range or for special demands. It is suitable for indoor and outdoor applications. If humidity penetrates through the sticked medias, thereby the adhesive force is reduced. During drying process the adhesion reconstructs itself.

Due to the multiplicity of possible influences on the stuck together product no information of a minimum durability or a maximum stress can be provided.