

## EMBLEM Polypropylen Lamination Film Sand 70 FR

EMBLEM Polypropylene Lamination Film Sand 70 FR is a matt, slightly textured protective laminate for print finishing in the graphic arts industry. The slightly structured sand surface is certified with slip resistance class R11. The adhesive enables fast and effective processing when laminating from a roll.

Matchcode:	<b>POPLAMSA70FR</b>
Material:	polypropylene
Finish:	matt, slightly textured, scratch-resistant sand surface
Colour:	transparent
Thickness:	70 µm
Weight:	57 g/m <sup>2</sup>
Liner:	one-side siliconised kraft paper, 135 g/m <sup>2</sup>
Adhesive:	transparent, permanent, polyacrylate
Adhesion power:	9 N/25 mm on steel - 24 h -> 12
Printable:	Latex and UV inks
Temperature resistance:	-10 °C to +40 °C
Application temperature:	from 18 ° - 25 °C, humidity 40% - 65%
Fire behaviour:	flame retardant - B-s1,d0 - according to EN 13501 on mineral substrate
Durability:	5 years outdoors
Standard roll width:	900 / 1040 / 1370 mm
Standard roll length:	50 m
Lamination film:	face out
Storage:	cool and dry environment, at 15-25 °C, 50 % rel. humidity
Shelf life:	24 month in original boxes

Different printers, inks, resolutions and printing qualities result into numerous different printing parameters. In addition, there are numerous factors influencing processing and the application of our materials. For this reason, we cannot make specific statements as to drying times and maximum ink absorption. For this reason, we recommend you to perform own tests in order to verify the desired results. Our product specifications are not to be understood as legally binding guarantees assuring specific characteristics. Any liabilities and guarantees, as well as claims for compensation beyond the value of the product itself are excluded.