

EMBLEM Solvent Film Glossy Monomeric Grey Glue

SOFOGLMGG is a self-adhesive, monomeric calendered vinyl film with a glossy surface, covered on the back side with high quality coated Paper.

Main fields of application for SOFOGLMGG are short term signage and in and outdoor advertising.

Matchcode:	SOFOGLMGG
Material:	PVC film, monomeric
Finish:	glossy
Color:	white
Thickness:	100 μ m
Adhesive:	grey pigmented acrylate adhesive, solvent free, permanent
Liner:	siliconised kraftliner, 135 g/m ² ,
Adhesion:	16 N/25 mm acc. to Finat 1 (average value)
Lamination:	cool, warm
Temperature resistance:	-30°C to +80°C
Application temperature:	> +10°C
Standard roll width:	105 cm / 137,2 cm
Standard roll length:	50 m
Durability:	24 months outdoors under Central European climate conditions
Storage:	cool and dry at 15-25°C, 50% rel. humidity
Shelf life:	24 months in original packing

COMPATIBLE INKS:

Eco solvent:	yes	UVC:	yes
Solvent:	yes	Latex:	yes

Different printers, inks, resolutions and printing qualities result into numerous different printing parameters. In addition, there are numerous factors influencing processing and the application of our materials. For this reason, we cannot make specific statements as to drying times and maximum ink absorption. For this reason, we recommend you to perform own tests in order to verify the desired results. Our product specifications are not to be understood as legally binding guarantees assuring specific characteristics. Any liabilities and guarantees, as well as claims for compensation beyond the value of the product itself are excluded.

EMBLEM Solvent Film Glossy Monomeric Grey Glue

Description:

SOFOGLMGG is a self-adhesive, monomeric calendered vinyl film with a glossy surface, covered on the back side with high quality coated Paper.

EMBLEM Solvent Film Glossy Monomeric Grey Glue is printable with all common solvent, eco-solvent, latex and UVC inks. On the white, glossy surface you achieve water resistant prints. The average durability of the film used for outdoor applications is up to 2 years. This durability refers only to the film and adhesive. The durability of the prints depends on the used inks and other criteria in the further processing.

Processing:

SOFOGLMGG is for use on flat surfaces. The subsurfaces to be paste up with the film have to be free of dust and grease. Varnishes have to be cured completely. To check compatibility between the adhesive and the varnish the user is advised to make tests before application. We advise the use of lamination film also for solvent prints to protect them from abrasion. After printing it is necessary to wait for an outright drying and degasing of the print to avoid diffusion of the solvent which could damage the adhesive or may cause lumps or delamination.

To avoid fingerprints the use of cotton gloves is advised.

Application:

Short term signage and advertising for indoor and outdoor, displays and construction sign building-blackboard