

EMBLEM Water Wall Decoration 130

EMBLEM Water Wall Decoration 130 is a paper-based non-woven wallpaper for individual interior design. The soft, matt, white surface of the non-woven wallpaper can be printed with common water-based and latex inks. The EMBLEM WAWADE130 is processed like conventional non-woven wallpapers.

Matchcode:	WAWADE130
Material:	coated paper non-woven, free from glass fibres
Finish:	matt
Colour:	white
Weight:	130 g/m ² ±10 - ISO 536
Thickness:	240 µm ±25 - ISO 536
Opacity:	>85% - ISO 2469
CIE whiteness:	>90 %, D65/10° - ISO 2469
Application temperature:	+15 °C to +30 °C
Fire behaviour:	flame retardant - B - s1, d0 according to EN 13501 on plasterboard
Standard roll width:	914 / 1067 mm
Standard roll length:	30 m
Core diameter:	76 mm (3")
Storage:	cool and dry at 15-25 °C, 50 % rel. humidity
Shelf life:	24 month in original boxes

COMPATIBLE INKS:

Dye:	yes	Latex:	yes
Pigment:	yes		

Different printers, inks, resolutions and printing qualities result into numerous different printing parameters. In addition, there are numerous factors influencing processing and the application of our materials. For this reason, we cannot make specific statements as to drying times and maximum ink absorption. For this reason, we recommend you to perform own tests in order to verify the desired results. Our product specifications are not to be understood as legally binding guarantees assuring specific characteristics. Any liabilities and guarantees, as well as claims for compensation beyond the value of the product itself are excluded.

EMBLEM Water Wall Decoration 130

Description:

EMBLEM Water Wall Decoration 130 is a paper-based non-woven wallpaper for individual interior design. The soft, matt, white surface of the non-woven wallpaper can be printed with common water-based inks and latex inks. Waterproof prints are only achieved when using pigment inks. The coating of EMBLEM WAWADE130 enables fast drying with good colour saturation and brilliant photorealistic prints. It is dimensionally stable, crack-bridging and easy to apply. The wallpaper adheres to smooth, slightly rough wall surfaces or plasters painted with dispersion paint. Dry strippability is supported by a coating on the reverse side.

The product is free of PVC and plasticisers. It is flame retardant according to EN 13501 and can also be used indoors.

Processing:

The prints can be used un laminated indoors as decoration.

For further processing as decorative wallpaper, the usual procedures for wallpapering should be followed. The substrate must be dry, clean, firm, absorbent and smooth. The wallpaper is usually applied using the wall pasting technique, in which the wall is pasted. If there are several panels, they are applied edge to edge. If necessary, a double seam cut can be made when the wall is dry. Press down the panels with a foam rubber roller or wallpaper brush until bubble-free. Remove leaking paste immediately with a moistened cloth or sponge.

For applying the wallpaper, we recommend commercially available paste for non-woven wallpapers such as Methylan Direct for non-woven wallpapers.

Application:

Typical applications for EMBLEM WAWADE130 are individual room designs for living spaces, children's rooms, shopping centres, museums, trade fair construction, commercial spaces, hotels and restaurants.